



Shades of Blue Sound Reinforcement and Lighting Rider – 12 Performers

Front of House System (FOH)

- Midas M32 or Behringer X32 FOH board capable of 32 separate channels, dedicated to Liquid Blue. Mixing console to have 10 aux sends if no separate monitor board.
- High quality equalizers for Channels, Mains and Monitors.
- Amps, crossovers, and speakers for full range (bi or tri amp) live sound reinforcement, applicable to venue and audience size. Place subs on or near the dance floor.
- FOH sound and/or Monitor engineers to be provided by sound reinforcement company.

Monitors

- Ten on stage monitor wedges with adequate power and EQ.
- Two Side Fill monitors with adequate power and EQ.

Microphones and Stands

- Eight drum microphones and stands as needed for standard drum kit.
- One microphone for guitar amp.

Wireless Microphones

- Six professional quality, frequency agile handheld wireless microphones, with wireless mic clips and boom type mic stands.

LED Monitors

- Two widescreen 21" LED monitors without stands and two 30 foot VGA cables with male connectors on both ends.

Stage Power

- Two 20-amp circuits, one at the back and one at the front.

Lighting

- Intelligent DMX controlled upstage and downstage LED Stage Wash, 4+ Lekos focused for face lighting, and a minimum of 4 upstage moving head fixtures. Includes Light Tech operator.

Questions? Contact Michael Vangerov at michael@vantasticsound.com or 619.808.2009 (text only)
Skype: Michael.Vangerov



Mixing Notes

- We want to have all line checks and a basic monitor mix complete by the scheduled time of the Full Band sound check and at that point just play full songs to dial in the monitors and FOH mix.
- The Keyboard Vocal mic volume should be as loud as the Lead Vocal mic in both the FOH and monitors. On some songs the lead vocal parts are sung from the keyboard.
- Each Vocalist will sing lead from their mic at some point during the performance.
- The Drummer has his own headphone monitor setup. If no wedge is available, he will need an aux mix sent to his monitor mixer which has a ¼" input.
- The Horn players generally only want their instruments in their monitors.
- Once the mix has been dialed in, there should only be small changes made as needed during the show.
- When making requested changes to the FOH and monitors, please make subtle changes.

Questions? Contact Michael Vangerov at michael@vantasticsound.com or 619.808.2009 (text only)
Skype: Michael.Vangerov